

7.2KW WALL BOX AC CHARGER

Type	TP-EVVA-220-1D
Dimension	300 x 1500 x 200 mm
Input Voltage	AC 240V
Rated Power	7.2 KW
Output Voltage	AC 240V
Output Current	32A
Weight	12 kg
Working Temperature	-20°C ~ +55°C
Relative Humidity	5% ~ 95%
Altitude	≤ 2000m
Material	Aluminum
IP Grade	IP 54
Cable Length	5m / Socket
Frequency	50Hz ± 1Hz
Communication Mode	Ethernet, GPRS, WIFI
Measurement Accuracy	1%
User Interface	LCD
Installation Method	Wall Box
Industry Standard	EN 61851-1:2011, EN 61000-6-1:2007, EN 61000-6-3:2007/A1:2011/AC:2012
Certification	CE



22KW WALL BOX AC CHARGER

Type	TP-EVVA-380-1F
Dimension	300 x 1500 x 200 mm
Input Voltage	AC 415V
Rated Power	22 KW
Output Voltage	AC 415V
Output Current	3 x 32A
Weight	12 kg
Working Temperature	-20°C ~ +55°C
Relative Humidity	5% ~ 95%
Altitude	≤ 2000m
Material	Aluminum
IP Grade	IP 54
Cable Length	5m / Socket
Frequency	50Hz ± 1Hz
Communication Mode	Ethernet, GPRS, WIFI
Measurement Accuracy	1%
User Interface	LCD
Installation Method	Wall Box
Industry Standard	EN 61851-1:2011, EN 61000-6-1:2007, EN 61000-6-3:2007/A1:2011/AC:2012
Certification	CE

