



# TELLUS POWER GREEN PEDESTAL AC CHARGERS

7.2kW – 22kW Series

## FEATURES

- Option for Dual and Single Connector
- Charges Two Vehicles Faster - No Power Sharing Required
- Low Cost, High-Performance Networked Electric Vehicle Charging Stations
- Touch Screen Display
- Supports OCPP 1.6J
- RFID Reader
- CE Certified

## Tellus Power Green AC Charger Specifications



Rated Power	1 x 7.2 kw	2 x 7.2 kw	1 x 22 kw	2 x 22 kw
Product #	TP-EVVA-220-1C	TP-EVVA-220-2D	TP-EVVA-380-1E	TP-EVVA-380-2B
Input    Output Voltage	208VAC to 240VAC    50 Hz		380VAC to 440VAC (3P+N+PE)    50 Hz	
Output current	1 x 32 A	2 x 32 A	1 x (3 x 32) A	2 x (3 x 32) A
Weight	~ 50 Kgs	~60 Kgs	~55 Kgs	~ 65 Kgs
Working Temp	-30°C to 55°C			
Relative Humidity	5% ~ 95%, Non-Condensing			
Altitude	≤3000m			
Material	Carbon Steel			
IP Grade	IP54			
Cable Length	5m / Socket (Type2)			
RFID system	ISO/IEC 14443 A/B			
Communication Protocol	OCPP 1.6J			
Dimension	300 x 200 x 1500 mm (W x D x H)			
Communication Mode	Ethernet (Standard)    3G/4G/WIFI (Optional)			
Meter Accuracy	1%			
User Interface	7 " Touch Screen			
Installation Type	Pedestal			
Industry Standard	EN 61851-1:2011, EN 61000-6-1:2007, EN 61000-6-3:2007/A1:2011/AC:2012			
Certification	CE			
Safety	Over Current, Short Circuit, Surge Protection, Leakage Current Protection			

