



TELLUS POWER GREEN WALLBOX AC CHARGERS

7.2 kW Series

FEATURES

- Option for Dual and Single Connector with wide range of power capacities
- Charges Two Vehicles Faster - No Power Sharing Required
- Affordable, Best Value EV Charging - Get a Dual Port Networked Charging Station for the price of the competition's Single Port Station.
- Low Cost, High-Performance Networked Electric Vehicle Charging Stations
- Screen Display with Voltage/Current/Time etc. Information.
- OCPP 1.6J compliant
- RFID Reader
- CE Certified

Tellus Power Green AC Wall Box Charger Specifications



Rated Power	1 x 7.2 kW (J1772)	2 x 7.2 kW (J1772)	1 x 7.2 kW (Type2)	2 x 7.2 kW (Type2)
Product #	TP2-7-220-1J	TP2-7-220-2J	TP2-7-240-1	TP2-7-240-2
Input Output Voltage	208VAC to 240VAC 50/60 Hz			
Connector Standard	SAE J1772		Type 2	
Output Current	1 x 32 Amps	2 x 32 Amps	1 x 32 Amps	2 x 32 Amps
Weight	12 – 20 kg			
Cable Length	5m / Socket (Type2)			
Working Temp	-30°C to 55°C			
Relative Humidity	5% ~ 95% Non-Condensing			
Altitude	≤3000m			
Material	Aluminum			
IP Grade	IP54			
RFID system	ISO/IEC 14443 A/B			
Communication Protocol	OCPP 1.6J			
Dimension (L x D x H)	410 x 230 x 150 mm			
Communication Mode	Ethernet (Standard) 3G/4G/WIFI (Optional)			
Meter Accuracy	1%			
User Interface	LCD Screen			
Installation Type	Wallbox			
Industry Standard	EN 61851-1:2011, EN 61000-6-1:2007, EN 61000-6-3:2007/A1:2011/AC:2012			
Certification	CE			
Safety	Over Current, Short Circuit, Surge Protection, Leakage Current Protection			
Accessories	Wall mounting brackets			

