



TELLUS POWER GREEN

TELLUS POWER GREEN DC FAST CHARGER 60 kW Charging Station

FEATURES

- Powerful Compact All-In-One DC Charger
- Simple Air-Cooled Power Modules
- Easy to Maintain
- Parallel Charging Feature
- Output Voltage of 1000VDC
- OCPP 1.6J
- Credit Card Reader
- Cord Management

Model : TP-EVPD-60kW



Tellus Power Green DC Fast Charger Specifications



Product #	TP5-60-480
Model #	TP-EVPD-60KW
Input	480VAC (3P+N+PE) 60Hz
Output Voltage	200 - 1000VDC
Output current	0 to 150A
FLA Breaker Rating	80A 100A
Connectors	CCS1 / NACS / CHAdeMO (Dual Connector)
Cyclic Charge Mode	CCS1 / NACS - 150A CHAdeMO – 125A
Parallel Charge Mode	30 kW per Port
Efficiency	≥94% at nominal output power
Power factor	> 0.98
Display	10" touch screen
Access Control	RFID : ISO/IEC 14443A/B Credit Card Reader (Optional)
Metering	DC kWh meter per each connector
Operating temperature	-22°F to 131°F (-30°C to 55°C)
Altitude	6500' (2000m)
Working Storage Humidity	≤ 95% RH ≤ 99% RH (Non-condensing)
Dimensions (L x D x H)	29.5" x 22.5" x 72"
Protective Class	NEMA 3S (IP54), IK10
Cooling system	Air cooling fans
Weight	617 lbs (280kgs)
Compliance	UL and CE Certified
DC Charge System	Mode 4 - IEC-61851, ISO-15118, DIN 70121 Mode 4 - CHAdeMO 0.9, 1.0
Charging cable	16ft (5m), Cable Retractor Included
Communication Protocol	Ethernet, 4G/WiFi OCPP 1.6J
Electrical Safety: GFCI	RCD 20 mA Type A
Electrical Safety: Surge Protection	20 kA
Electrical Safety General	Over Voltage, Under Voltage, Over Current, Missing Ground
Electrical Safety: Output Short	Output power disabled when output is short circuited
Electrical Safety Temperature	Temperature Sensors @ Charge Coupler and Power Electronics
Emergency Stop	Emergency Stop Button Disables Output Power
Regulatory Compliance	UL-2202 EMC: EN 61000-6-1:2007, EN 61000-6-3:2007/A1:2011/AC:2012

