



TELLUS POWER GREEN DC FAST CHARGER

30 kW Charging Station



- ✓ Upto 100A with 1000VDC
- ✓ 4G / Wi-Fi / Ethernet connectivity
- ✓ 7" Touch screen display
- ✓ OCPP 1.6J
- ✓ CCS1 Connector
- ✓ Wall Mount / Pedestal (Optional) Installation
- ✓ Easy Installation (Indoor / Outdoor)
- ✓ Cord Management (Optional)

Model :
TP-EVPD-30kW

TELLUS POWER GREEN DC FAST CHARGER

30 kW DC Fast Charging Station



**Model :
TP-EVPD-30kW**



Product #	TP5-30-480-1
Model #	TP-EVPD-30kW
Input Voltage	480VAC (3P+N+PE), 60Hz
FLA Breaker Rating	40A 50A
Output Voltage	150 to 1000VDC
Output Current	Upto 100A
Connector(s)	CCS1
Efficiency	≥94% at nominal output power
Power Factor	> 0.98
Operating Temperature	22°F to 131°F (-30°C to 55°C)
Working Storage humidity	≤ 95% RH ≤ 99% RH (Non-condensing)
Altitude	< 6600ft (2000m)
Display	7" touch screen
RFID system	ISO IEC 14443A/B
Dimensions (l x d x h)	21" x 12" x 27"
Protective Class	NEMA 3S, IK 10
Cooling System	Air cooled
Weight	176 lbs (80kg)
Charging Protocol	Mode 4, IEC-61851, ISO-15118, DIN SPEC 70121
Length of charging cable	16ft (5m)
Communication Protocol	Ethernet / 4G Wi-Fi OCPP 1.6J
Electrical Safety: GFCI	RCD 20 mA Type A
Electrical Safety: Surge Protection	20 kA
Electrical Safety General	Over Voltage, Under Voltage, Over Current, Missing Ground
Electrical Safety: Output Short	Output power disabled when output is short circuited
Electrical Safety Temperature	Temperature Sensors @ Charge Coupler and Power Electronics
Emergency Stop	Emergency Stop Button Disables Output Power
Regulatory Compliance	UL-2202 CSA C22.2#107.1:2016 EMC: EN 61000-6-1:2007, EN 61000-6-3:2007/A1:2011/AC:2012